

# DUO CM 5.0 A

## LIFTING TECHNOLOGY



## DUO

VP 250238

Scissors Lift with 5000 kg Load Capacity

### DESCRIPTION:

- ♦ Scissor lift for on-ground installation
- ♦ Very robust and well-established design with a high vehicle throughput and optimum service life in mind
- ♦ High lateral stability and bending strength, so also suited to precise wheel alignment
- ♦ Runways equipped with pre-integrated guide rail for axle lift
- ♦ Latches and cylinder racks as extra safety feature
- ♦ Cables and hydraulic hoses installed safely within scissor pipes
- ♦ An elevated lifting height in excess of 2.1 m makes repair works and access easier
- ♦ EMERGENCY OFF function in the case of power failure
- ♦ Additional anti-corrosion treatment of lock seams, cavity sealing
- ♦ Varnished with high-quality powder coating: gentian blue, RAL 5010
  
- ♦ Automatic synchronisation of runways and the optional wheel-free jack
- ♦ Protected within the lifting cylinders, the maintenance-free integrated displacement measurement encoder ('linear-absolute measuring system') eliminates the need for light barriers for synchronisation monitoring and electric switches for lift height detection
- ♦ High level of safety due to immediate switch-off in case of (one-sided) collision with obstacle at minimum height difference
- ♦ Crushing and shearing protection due to CE stop
- ♦ Stops automatically upon rising to desired lifting height with custom programmable breakpoint
- ♦ Robust membrane keyboard
  
- ♦ Double latch option for wheel alignment for additional stability within the scissors arm (not possible in conjunction with wheel-free jack)
- ♦ DUO-SPEED option for short lifting / lowering times

### STANDARD DELIVERY:

- ♦ Scissor lift, type: DUO CM 5.0 A
- ♦ Operation desk with control and hydraulic unit
- ♦ Lockable main switch
- ♦ Cover plates for cables and hydraulic hoses
- ♦ 2 long drive-on ramps, 2 roll bars
- ♦ 2 pneumatic quick-action couplings installed on runway
- ♦ 8 rope loops to be used as a transport aid
- ♦ Operating manual and test log
- ♦ EC CE declaration of conformity
- ♦ Transport packaging

## TECHNICAL DATA:

Load capacity CE	5000 kg
Load capacity CE with wheel-free jack	5000 kg
Lifting height max.	2140 mm
Raising / Lowering time (load-dependent) approx.	50 s / 40 s
Drive-on height	290 mm
Full travel	1850 mm
Operating pressure	190 bar
Motor power	2,5 kW
Fuse gG	16 A
Power supply	3/N/PE 400 V 50 Hz
Dimensions packaging (L x W x H)	5300 mm x 800 mm x 800 mm
Dimensions total (L x W x H)	6800 mm x 2210 mm x 290 mm
Runway dimensions (L x W x H)	5200 mm x 630 mm x 176 mm
Weight	3000 kg
Weight incl. packaging	3200 kg
Hydraulic fluid quantity (not included in standard delivery)	40 l

## ACCESSORIES:

VZ 990450	Mains power supply 3/N/PE 380-400 V 60 Hz
VZ 990451	Mains power supply 3/N/PE 230 V 50 Hz
VZ 985060	Manual lowering function DUO CM
VZ 975013	Runways with granulate coating
VZ 970028	Lifting/Lowering Time 20/20s (4,2 t);30/30s (5,0t)
VZ 970029	lifting/lowering time 12/12s (4,2t); 15/18s (5,0t)
VZ 975181	Compressed-Air Servicing Unit
VZ 970012	Wheel-Free Jack 4
VZ 975074	Plug-In Type Hard Rubber Chocks
VZ 975069	Plastic chocks set 47 x 132 x 340 mm
VZ 990432	LED Illuminant 2 pieces
VZ 990433	LED Illuminant 4 pcs
VZ 990012	Shockproof socket 230 V
VZ 990029	Light barrier s. device to avoid c. with ceiling
VZ 990423	Pinch Point Protection DUO
VZ 970161	External Operating Unit DUO CM
VZ 970153	Compensating Plates for Level Adaption WFJ
VZ 970010	Aluminium Step Ramp for Low-Lying Vehicles
VZ 970019	Corrugated metal exit ramp, f. above-floor lifts
VP 985007	PMS 3/X
VP 985024	PMS 3/XL
VZ 995021	Install. costs f. stand. install. of play detector
VZ 990199	Safety switch f. lift in conj. with brake testers
VZ 970135	Mechanical Locks
VZ 970042	Double safety catch f. under-carriage alignment
VZ 975032	Compensating plates without turning plates
VZ 975455	Granular Coating for Turning Plates
VZ 975027	Sliding plate covers, standard aluminium
VZ 975454	Gran. coating f. comp. plates f. lift without WFJ
VZ 970159	Sliding Plates 1800 mm length
VZ 970148	Compens. & Support Plates with 5,2 m
VZ 970149	Set of compensating plates 5200 mm
VM 999035	Hydraulic Oil (HLP-D 22) per litre
VM 999014	Hydraulic Oil (HLP 32) Biodegradable
VM 999047	Assembly Material
VM 999061	Assembly Material with wheel free jack
VM 999049	Assembly material additional